

MLX90416

No-Hall 1-coil motor driver for high speed fans

Product Abstract

General description

Features & benefits

- Sensorless 1-coil No-Hall technology
- Open and closed loop speed control:
 - Up to 40k mRPM (for 2 pole-pair motors)
 - $\pm 1.5\%$ closed loop speed accuracy
 - Soft-switching
 - Lead angle control
- Configurable motor start & stop options:
 - Forward windmilling
 - Brake & start
- Integrated bridge driver
 - 135 mOhm (HS+LS)
 - Programmable current limit up to 4.0 A
 - 8.0 A braking current
 - Integrated supply clamp
- Operating range:
 - Supply voltage range from 6.7 V to 27.6 V
 - Junction temperature from -40 °C to 150 °C
- Extensive programmability (MTP)
 - Sleep mode option
 - 8-point configurable speed curves
 - Synthesized FG output for easy retrofitting of legacy 3-phase solutions
- Protections & Diagnostics
 - LRP / UVP / OCP / TSD
 - Hot unplug handling
- Package RoHS compliant
 - DFN10 3.5x3 mm² with exposed pad

Applications examples

- 24 V Industrial fans
- 24 V Fans for home appliance & white goods
- General 24 V fans & pumps up to 60 W

Available support & tools

- www.melexis.com/technical-inquiry
- www.melexis.com/FanDriverEVB2
- www.melexis.com/FanDriverProgrammerB

Description

The MLX90416 is a member of the No-Hall sensorless 1-coil BLDC motor driver IC's for driving 24 V applications. It can be configured for a wide range of applications and supports replacing legacy sensorless 3-phase motors.

The device drives 12 | 24 V 1-coil motors, typically without the need for an external TVS for protection. It integrates two half bridges with very low RDSon, supporting 8 A braking current and a programmable current limit up to 4 A.

The MLX90416 is controlled via a PWM input, and provides speed feedback through a programmable FG output. Extensive speed curve fitting is available with 8 configuration points, up to 40k mRPM (for 2 pole-pair motors).

The non-volatile memory can be programmed through I2C and is "Multiple Times Programmable"

The IC features a wide range of protections, including: "Locked Rotor Protection", "Under Voltage Protection" with hot unplug handling, "Thermal Shut Down" and "Over Current Protection".

Plug-and-play prototyping: a motor parameter extraction tool is available for fast validation.




Figure 1 – Functional diagram

MLX90416

No-Hall 1-coil motor driver for high speed fans

Product Abstract



Ordering information

Product order code	Temperature	Package	IC version code	CLIM _{MAX}	Packing
MLX90416KLD-AAA-004-RE	-40 to 150 °C	DFN10	AAA-00	4.0 A	Reel
MLX90416KLD-AAA-002-RE	-40 to 150 °C	DFN10	AAA-00	2.8 A	Reel

Table 1 – Product codes

1 Conditions and specifications

1.1 Absolute Maximum Ratings (AMR)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Supply voltage	V _{DDcont}	-0.3		29	V	Externally applied
Peak motor braking current	I _{PHASE_brk}			I _{ocp_min}	A	During initial braking ¹ , <500 ms
FG, IO1 output voltage	V _{FG}	-0.3		29	V	
SPD, IO2 voltage	V _{PWM}	-0.3		V _{DD} + 0.3	V	
OUT1, OUT2 voltage	V _{OUT}	-1		V _{DD} + 1.0	V	During PWM switching dead time
OTP write temperature	T _{OTPwrite}			50	°C	3x OTP pages
Maximum ambient temperature	T _{AMB}	-40		125	°C	¹
Maximum junction temperature	T _J	-40		150	°C	¹
Storage temperature range	T _s	-55		165	°C	
ESD Sensitivity – HBM	V _{HBM}			4000	V	HBM according to JS-001
ESD Sensitivity – CDM	V _{CDM}			1000	V	CDM according to JS-001

Table 2 – Absolute Maximum Ratings

Exceeding the absolute maximum ratings may cause permanent damage.

Exposure to absolute maximum-rated conditions for extended periods may affect the device reliability.

1.2 Electrical operating conditions & specifications

Unless otherwise specified, the electrical specifications are valid at T_J 25 °C, and a supply voltage range from 6.7 to 24 V. All absolute timings, except for closed loop speed control are subject to RCO tolerances.

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
VDD operating range	V _{DD}	6.7	12	27.6	V	
VDD degraded operating range	V _{DD_DEGR}	5.7		6.7	V	
VDD digital register preserved	V _{POR}		3.55	4.5	V	

Table 3 – Electrical operating conditions

¹ Maximum junction operating temperature should not be exceeded.

MLX90416

No-Hall 1-coil motor driver for high speed fans

Product Abstract

2 Pins description for DFN10 package

Pinout	Pin #	Name	I/O	Description
	1	IO1	I/O	IO1
	2	GND	Ground	Ground connection
	3	OUT1	Output	Motor coil connection 1
	4	GND	Ground	Ground connection
	5	OUT2	Output	Motor coil connection 2
	6	SPD	Input	<ul style="list-style-type: none"> PWM input SCL input for the I²C interface
	7	FG	I/O	<ul style="list-style-type: none"> FG output SDA input/output for the I²C interface
	8	IO2	I/O	IO2
	9	VDD	Supply	Power supply input voltage
	10	VDD	Supply	Power supply input voltage
	EP	EP	Ground	Exposed pad to be connected to GND

Figure 2 - DFN10 package pinout

Table 4 – DFN10 package pins description

3 Recommended application diagram

A decoupling capacitor should be placed as close as possible to the MLX90418 VDD and GND pins.




Figure 3 – Recommended application diagram




Figure 4 – Reference layout


Component	Symbol	Value	Condition
Decoupling capacitor	C1	10 μ F	
Optional reverse polarity diode	D1		<ul style="list-style-type: none"> Optional component, in case reverse polarity protection is not guaranteed by polarity of the connector Component to be selected acc. to application voltage and current requirements

Table 5 – External components specifications for recommended application diagram

MLX90416

No-Hall 1-coil motor driver for high speed fans


Product Abstract



4 Package, IC handling and assembly

4.1 Package information


4.1.1 Package DFN10 dimensions



NOTE :
 1. ALL DIMENSIONS ARE IN MILLIMETERS (mm)
 2. EXPOSED TIE BAR SHOULD BE KEPT FREE FROM SOLDER.

SYMBOL	ALL DIMENSION ARE IN MILLIMETERS		
	MINIMUM	NOMINAL	MAXIMUM
A	0.80	0.85	1.00
A1	0	0.02	0.05
A3	0.20 REF		
D	3.40	3.50	3.60
E	2.90	3.00	3.10
P1	1.80	1.90	2.00
P2	2.20	2.30	2.40
L	0.35	0.40	0.45
K	0.40 REF		
b	0.25	0.30	0.35
e	0.55 BSC		

Figure 5 – Package outline dimensions



NOTE :
 1. ALL DIMENSIONS IN MILLIMETERS (mm) UNLESS NOTED OTHERWISE
 2. PIN 2 AND PIN 4 (ELECTRICAL GROUND) NEED TO BE CONNECTED TO EXPOSED PAD.

Figure 6 – Recommended land pattern

5 Revision history

Revision	Date	Change history
1.0	25-Jun-2024	▪ First release

Table 6 – Revision history

6 Disclaimer

The content of this document is believed to be correct and accurate. However, the content of this document is furnished "as is" for informational use only and no representation, nor warranty is provided by Melexis about its accuracy, nor about the results of its implementation. Melexis assumes no responsibility or liability for any errors or inaccuracies that may appear in this document. Customer will follow the practices contained in this document under its sole responsibility. This documentation is in fact provided without warranty, term, or condition of any kind, either implied or expressed, including but not limited to warranties of merchantability, satisfactory quality, non-infringement, and fitness for purpose. Melexis, its employees and agents and its affiliates' and their employees and agents will not be responsible for any loss, however arising, from the use of, or reliance on this document. Notwithstanding the foregoing, contractual obligations expressly undertaken in writing by Melexis prevail over this disclaimer.

This document is subject to change without notice, and should not be construed as a commitment by Melexis. Therefore, before placing orders or prior to designing the product into a system, users or any third party should obtain the latest version of the relevant information.

Users or any third party must determine the suitability of the product described in this document for its application, including the level of reliability required and determine whether it is fit for a particular purpose.

This document as well as the product here described may be subject to export control regulations. Be aware that export might require a prior authorization from competent authorities. The product is not designed, authorized or warranted to be suitable in applications requiring extended temperature range and/or unusual environmental requirements. High reliability applications, such as medical life-support or life-sustaining equipment or avionics application are specifically excluded by Melexis. The product may not be used for the following applications subject to export control regulations: the development, production, processing, operation, maintenance, storage, recognition or proliferation of:

1. chemical, biological or nuclear weapons, or for the development, production, maintenance or storage of missiles for such weapons;
2. civil firearms, including spare parts or ammunition for such arms;
3. defense related products, or other material for military use or for law enforcement;
4. any applications that, alone or in combination with other goods, substances or organisms could cause serious harm to persons or goods and that can be used as a means of violence in an armed conflict or any similar violent situation.

No license nor any other right or interest is granted to any of Melexis' or third party's intellectual property rights.

If this document is marked "restricted" or with similar words, or if in any case the content of this document is to be reasonably understood as being confidential, the recipient of this document shall not communicate, nor disclose to any third party, any part of the document without Melexis' express written consent. The recipient shall take all necessary measures to apply and preserve the confidential character of the document. In particular, the recipient shall (i) hold document in confidence with at least the same degree of care by which it maintains the confidentiality of its own proprietary and confidential information, but no less than reasonable care; (ii) restrict the disclosure of the document solely to its employees for the purpose for which this document was received, on a strictly need to know basis and providing that such persons to whom the document is disclosed are bound by confidentiality terms substantially similar to those in this disclaimer; (iii) use the document only in connection with the purpose for which this document was received, and reproduce document only to the extent necessary for such purposes; (iv) not use the document for commercial purposes or to the detriment of Melexis or its customers. The confidentiality obligations set forth in this disclaimer will have indefinite duration and in any case they will be effective for no less than 10 years from the receipt of this document.

This disclaimer will be governed by and construed in accordance with Belgian law and any disputes relating to this disclaimer will be subject to the exclusive jurisdiction of the courts of Brussels, Belgium.

The invalidity or ineffectiveness of any of the provisions of this disclaimer does not affect the validity or effectiveness of the other provisions. The previous versions of this document are repealed.

Melexis © - No part of this document may be reproduced without the prior written consent of Melexis. (20-June-24)

IATF 16949 and ISO 14001 Certified

Happy to help you! www.melexis.com/contact